<u> FUNE</u>

ELECTRIC MODEL



Also in High Voltage: 3 phase, 380-480V, 30 Amp max

liso in High Voltage: 3 phase, 3	60-460 v , 30 Amp ii
Horsepower	15 HP / 11 KW
Voltage (50/60 Hz)	3 phase x 200-240V
Amperage (max)	45 Amp
Dedicated Breaker Requirement	45 Amp
Generator Recommendation	33 KW
Weight of Machine	838 lbs / 380 kg
Grinding Pressure Weights UP	443 lbs / 201 kg
Grinding Pressure Weights DOWN	522 lbs / 237 kg
Attachment Speed	300-1100 rpm
Working Width	25.8in / 655mm
Tool Holder Diameter	3x9in / 3x225mm
Vacuum Hose Port	Camlock E250
Water feeding (from tank or hose connection)	Under machine
Water tank capacity	5.2gal / 20L
Cable Length	57 ft / 17.4 m
Machine Size LxWxH	71x28x48 in 180x71x122 cm
Crate Size LxWxH	58x33x57 in 148x84x146 cm

L25LE

- DUST-PROOF PLANETARY DRIVE WITH UPGRADED CHAIN
- NEW & IMPROVED WATER SYSTEM WITH 2 VALVES FOR USING WATER FROM TANK OR EXTERNAL SOURCE
- ADDED PROTECTION AGAINST EXCESSIVE VOLTAGE
- EASY-TO-USE INTEGRATED WEIGHTS
- IMPROVED DUST COLLECTION EFFICIENCY
- LED LIGHTS IN FRONT & BACK
- NEW ADJUSTABLE HANDLE BAR
- CHARGING PHONE STATION WITH DUAL USB 2.0 PORTS
- A DURABLE STAINLESS STEEL CUP HOLDER















