



LAVINA



L25RE REMOTE-CONTROLLED



Action required	Time left	
Seal Replacement	400 h	Set
Chain Inspection	300 h	Set
Belt Inspection	400 h	Set
Tooling Inspection	200 h	Set

Log in Log off

Horsepower	10 HP / 7.5 KW
Voltage (50-60 Hz)	1 or 3 ph x 200-240V
Amperage (max)	45 Amp
Dedicated Breaker Requirement	45 Amp
Generator Recommendation	33KW
Weight of Machine	983 lbs / 446 kg
Grinding Pressure Weights UP	364 lbs / 165 kg
Grinding Pressure Weights DOWN	436 lbs / 198 kg
Attachment Speed	300-1100 rpm
Working Width	25in / 655mm
Tool Holder Diameter	3x9in / 3x225mm
Tool Diameter	3x9in / 3x225mm
Vacuum Hose Port	Camlock E250
Water feeding (from tank or hose connection)	Under machine
Water tank capacity	5.2gal / 20L
Cable Length	57 ft / 17.4 m
AMG Battery	12 V/2x7 AH
RC Battery (rechargeable)	AA 1.2V
Machine Size LxWxH	76x28x47 in 197x71x120 cm
Crate size LxWxH	62x29x43 in 157x73x110 cm

NEW INTELLIGENT REMOTE CONTROL

Precise control over the machine - two sensitive thumbsticks control its position and offset, including integrated mapping on the offset. A wide range of functions. Super light and easy to use with ergonomic rubber grip.

INTUITIVE TOUCHSCREEN PANEL / HMI

Our new HMI provides essential operating information and implements operators' instructions. HMI functionality includes:

- indications of power supply and power consumption,
- machine load and hours worked,
- tool holder rpm and option to choose rpm setting with tool input,
- water supply and lights activation,
- maintenance reminders,
- password activation and shutoff, etc.