

ELECTROPLATED DIAMOND SCREENS FOR SPOT REPAIR AND RESTORATION



Red Orange Gold 220 grit 400 grit 600 grit

AN EFFICIENT AND VERSATILE SOLUTION FOR SPOT REPAIR AND FLOOR RESTORATION.

PROPRIETARY ELECTROPLATING TECHNOLOGY FOR LONG, EFFECTIVE SCREEN LIFE

- Great for preparing damaged floors prior to polishing using diamond pads.
- Repair traffic patterns and stains before they become more costly issues.
- Significantly longer life vs other diamond restoration systems.
- No special equipment required use with your existing floor maintenance equipment for low start-up costs.
- Use in-house maintenance crews or existing maintenance contractor for light restoration work, without the need for special training.
- For best results use the screens wet with water or a neutral cleaner. Clean the screens after each use by hosing with clear water.
- Offered in 13, 14, 15, 16, 17, 18, 20, 21, 24 and 27 inch sizes.







How to use the diamond screens

Use the screens with standard speed equipment (single disc or automatic scrubbers) up to 350 rpm.

Use the screens with water or a cleaning solution. Always clean the screens after each use by hosing with clear water.

Use the screens in multiple applications as long as they remain functional. Screens can cover up to 30,000 sf when used with a standard 350 RPM floor machine.

A sealer or densifier can be used after completion of floor prep with screens and before the polishing steps using diamond pads.

Use the screens with any standard same sized floor pad. Secure to the pad driver using a center hole lock. The gray ring that comes with the screens is a safety ring and it goes in the indented area of the screen for added stability during use.