NEW! L25LS7



MODEL	L25LS7
Power	15 hp / 11 kW
Voltage* (50-60 Hz)	3 phase, 200-240V
Amperage (max)	45 Amp
Also in High Voltage	3ph, 400-480V, 30 Amp
Weight of Machine	884 lbs / 400 kg
Grinding Pressure	342-520 lbs 155-240 kg
Tool Holder RPM	400-1100 rpm
Working Width	26.5 in / 673 mm
Tool Holders (Left Rotation)	3x9 in / 3x225 mm
Vacuum Hose Port	Camlock E250
Water Feed (tank or hose connection)	gravity-fed
Water Tank	5.2 gal / 20 L
Cable Length	57 ft / 17.4 m
Machine Size L x W x H	84 x 29 x 46 in 214 x 72 x 116 cm

SEALED, DUST-PROOF Grinding Head



- Completely redesigned chain-driven planetary drive with no chain tensioner.
- New stronger timing belt.
- Upgraded shafts, seals and bearings.
- New lighter timing pulleys for better power transmission.
- New 2-piece aluminum main belt housing with belt inspection cover for longer belt life and less maintenance.

ALL-NEW FRAME



- New weights for faster position change.
- Redesigned frame allowing easier tool changes.
- New handle design faster adjustability & more positions.
- Rubber bushing at head attachment points for less vibrations.
- New, heavy-duty rubber tires.
- Water tank cap & new storage compartment.
- Adjustable LED lights.

*Also in High Voltage: 3 phase, 400-480V, 30 Amp