IAVINA




Motor Power	7.5 KW
Voltage (50-60 Hz)	3 ph x 380-400V
Amperage	15 Amp
Dedicated Breaker Requirement	15 Amp
Recommended dust extractor - V25EU	
Weight of Machine	446 kg
Grinding Pressure Weights UP	165 kg
Grinding Pressure Weights DOWN	198 kg
Attachment Speed	300-1100 rpm
Working Width	655 mm
Tool Holder Diameter	3x225 mm
Vacuum Hose Port	Camlock E250
Water feeding (from tank or hose connection)	Under machine
Water tank capacity	20L
Cable Length	17.4 m
AMG Battery RC Battery (rechargeable)	12 V/2x7 AH AA 1.2V
Machine Size LxWxH	197x71x120 cm
Crate size LxWxH	157x73x110 cm

L25REU REMOTE-CONTROLLED









NEW INTELLIGENT REMOTE CONTROL

Precise control over the machine - two sensitive thumbsticks control its position and offset, including integrated mapping on the offset. A wide range of functions. Super light and easy to use with ergonomic rubber grip.

INTUITIVE TOUCHSCREEN PANEL / HMI

Our new HMI provides essential operating information and implements operators' instructions. HMI functionality includes:

- indications of power supply and power consumption,
- · machine load and hours worked,
- tool holder rpm and option to choose rpm setting with tool input,
- · water supply and lights activation,
- maintenance reminders,
- · password activation and shutoff, etc.

See back page for more features.

L25REU

- DUST-PROOF PLANETARY DRIVE WITH UPGRADED CHAIN
- NEW, SIMPLIFIED WATER SYSTEM WITH 2 VALVES FOR USING WATER FROM TANK OR EXTERNAL SOURCE
- ADDED PROTECTION AGAINST EXCESSIVE VOLTAGE
- EASY-TO-USE INTEGRATED WEIGHTS
- IMPROVED DUST COLLECTION EFFICIENCY
- LED LIGHTS IN FRONT & BACK
- NEW ADJUSTABLE HANDLE BAR
- NEW THIRD WHEEL DESIGN
- CHARGING PHONE STATION WITH DUAL USB 2.0 PORTS
- A DURABLE STAINLESS STEEL CUP HOLDER

















