

**MORE TORQUE BETTER CONTROL LESS MAINTENANCE** 

Propane Engine	Kawasaki FX600V
Engine Capacity	19 hp / 14.2 kW 603 cc, 36.8 cu. in.
Weight of Machine	908 lbs / 412 kg
Grinding Pressure	370-556 lbs /
integrated weights w/ 4 positions	168-252 kg
Tool Holder RPM	425-765 rpm
Engine RPM	2000-3600 rpm
Working Width	30.8 in / 783 mm
Tool Holder Diameter	3x13.2in / 3x335mm
Application	wet or dry
Vacuum Hose Port	Camlock E300
Water Feeding from tank, or hose connection	gravity-fed
Water Tank Capacity	5.2 gal / 20 L
Propane Tank Capacity	20 lbs / 9 kg

86x32x46 in

218x82x116 cm

**Machine Size** 

LxWxH









## SEALED, DUST-PROOF GRINDING HEAD FOR LONGER SERVICE LIFE

- Completely redesigned chain-driven planetary drive with no chain tensioner.
- New stronger timing belt.
- Upgraded shafts, seals and bearings.
- New lighter timing pulleys for better power transmission.
- New 2-piece aluminum main belt housing with belt inspection cover for longer belt life and less maintenance.



## ALL-NEW FRAME DESIGN AND FEATURES TO MAKE YOUR WORK EASIER

- New weights for faster position change.
- Redesigned frame allowing easier tool changes.
- New handle design faster adjustability & more positions.
- Rubber bushing at head attachment points for less vibrations.
- New, heavy-duty rubber tires.
- Water tank cap & new storage compartment.
- Adjustable LED lights with magnetic attachment.





