AVING

L25S7



L25S7

Power 10 hp / 7.5 kW

Voltage 1 or 3 phase, (50-60 Hz) 200-240V

Amperage (max) 30 Amp

Weight of Machine 871 lbs / 395 kg

Grinding Pressure 329-514 lbs / integrated weights w/4 pos 149-233 kg

Tool Holder RPM 400-1100 rpm

Working Width 26.5 in / 673 mm

Tool Holders (Left Rotation) 3x9 in / 3x225 mm

Vacuum Hose Port Camlock E250

Water Feed

MODEL

(tank or hose connection)

gravity-fed

Water Tank 5.2 gal / 20 L

Cable Length 57 ft / 17.4 m

Machine Size 84 x 29 x 46 in / L x W x H 214 x 72 x 116 cm



SEALED, DUST-PROOF GRINDING HEAD

- Completely redesigned chain-driven planetary drive.
- New stronger timing belt.
- Upgraded shafts, seals and bearings.
- New lighter timing pulleys for better power transmission.
- New 2-piece aluminum main belt housing with belt inspection cover for longer belt life and less maintenance.



ALL-NEW FRAME



- New weights for faster position change.
- Redesigned frame allowing easier tool changes.
- New handle design faster adjustability & more positions.
- Rubber bushing at head attachment points for less vibrations.
- New, heavy-duty rubber tires.
- Water tank cap & new storage compartment.
- Adjustable LED lights.