

# LAVINIA

## L30S7



### SEALED, DUST-PROOF GRINDING HEAD



- Completely redesigned chain-driven planetary drive.
- New stronger timing belt.
- Upgraded shafts, seals and bearings.
- New lighter timing pulleys for better power transmission.
- New 2-piece aluminum main belt housing with belt inspection cover for longer belt life and less maintenance.

### ALL-NEW FRAME



- New weights for faster position change.
- Redesigned frame allowing easier tool changes.
- New handle design – faster adjustability & more positions.
- Rubber bushing at head attachment points for less vibrations.
- New, heavy-duty rubber tires.
- Water tank cap & new storage compartment.
- Adjustable LED lights.

<b>MODEL</b>	<b>L30S7</b>
<b>Power</b>	<b>15 hp / 11 kW</b>
<b>Voltage (50-60 Hz)</b> Also in High Voltage	<b>3 ph, 200-240V, 45 A</b> <b>3 ph, 400-480V, 30A</b>
<b>EU model L30ES7</b>	<b>3 ph, 380-400V, 30A</b>
<b>Dedicated Breaker</b>	<b>45 Amp</b>
<b>Weight of Machine</b>	<b>998 lbs / 453 kg</b>
<b>Grinding Pressure</b>	<b>460-619 lbs</b> <b>209-289 kg</b>
<b>Tool Holder RPM</b>	<b>400-765 rpm</b>
<b>Working Width</b>	<b>30.8 in / 783 mm</b>
<b>Tool Holder Diameter</b>	<b>3x13.2in / 3x335mm</b>
<b>Vacuum Hose Port</b>	<b>Camlock E300</b>
<b>Water Feed</b>	<b>tank or hose connection</b>
<b>Water Tank</b>	<b>5.2 gal / 20 L</b>
<b>Cable Length</b>	<b>57 ft / 17.4 m</b>
<b>Machine Size</b> L x W x H	<b>85 x 32 x 46 in</b> <b>216 x 82 x 116 cm</b>