

L25LS7



S7 SERIES



| | |
|--|---|
| MODEL | L25LS7 |
| Power | 15 hp / 11 kW |
| Voltage (50-60 Hz) Also in High Voltage | 3 phase, 200-240V, 45 A 3phase, 400-480V, 30 A |
| European Model L25LES7 | 3 phase, 400-480V, 30A |
| Dedicated Breaker | 45 Amp |
| Weight of Machine | 970 lbs / 440 kg |
| Grinding Pressure with integrated weights | 436-597 lbs 198-271 kg |
| Tool Holder RPM | 400-1100 rpm |
| Working Width | 26.5 in / 673 mm |
| Tool Holders (Left Rotation) | 3x9 in / 3x225 mm |
| Vacuum Hose Port | Camlock E250 |
| Water Feed | tank or hose connection |
| Water Tank | 5.2 gal / 20 L |
| Cable Length | 57 ft / 17.4 m |
| Machine Size L x W x H | 84 x 29 x 46 in 214 x 72 x 116 cm |

NEW FRAME AND A SEALED, DUST-PROOF GRINDING HEAD

- Completely redesigned chain-driven planetary drive.
- New stronger timing belt.
- Upgraded shafts, seals and bearings.
- New lighter timing pulleys for better power transmission.
- New 2-piece aluminum main belt housing with belt inspection cover for longer belt life.
- New weights for faster position change.
- Redesigned frame allowing easier tool changes.
- New handle design – faster adjustability & more positions.
- Rubber bushing at head attachment points for less vibrations.
- Water tank cap & new storage compartment.
- Adjustable LED lights.