

L25S7



S7 SERIES



MODEL	L25S7
Power	10 hp / 7.5 kW
Voltage (50-60 Hz) Amperage	1 or 3 phase, 200-240V, 30 Amp (max)
European Model L25LES7	3 phase, 400-480V, 30A
Dedicated Breaker	30 Amp
Weight of Machine	871 lbs / 395 kg
Grinding Pressure with integrated weights	329-514 lbs / 149-233 kg
Tool Holder RPM	400-1100 rpm
Working Width	26.5 in / 673 mm
Tool Holders (Left Rotation)	3x9 in / 3x225 mm
Vacuum Hose Port	Camlock E250
Water Feed	tank or hose connection
Water Tank	5.2 gal / 20 L
Cable Length	57 ft / 17.4 m
Machine Size L x W x H	84 x 29 x 46 in 214 x 72 x 116 cm

NEW FRAME AND A SEALED, DUST-PROOF GRINDING HEAD

- Completely redesigned chain-driven planetary drive.
- New stronger timing belt.
- Upgraded shafts, seals and bearings.
- New lighter timing pulleys for better power transmission.
- New 2-piece aluminum main belt housing with belt inspection cover for longer belt life. New weights for faster position change. Redesigned frame allowing easier tool changes.
- New handle design – faster adjustability & more positions.
- Rubber bushing at head attachment points for less vibrations.
- Water tank cap & new storage compartment.
- Adjustable LED lights.